



NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Oregon South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water 1983-2001. MLLW is 0.93 feet below the North American Vertical Datum (NAVD 88) at North Bend RR Bridge.
 River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basin Commission, June 1968.
 The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general channel conditions existing at that time and is in support of channel maintenance only.
 ** Shoalest Sounding per Quarter per Reach
 STAFF GAGE: Nothing: 663401 Easting: 3929222
 CONDITION PREDREDGE POSTDREDGE

LEGEND

COOS BAY, OREGON
NORTH BEND TURN
 28 February 2024
 SCALE IN FEET
 0 300 600 900 1,200 1,500
 SUBMITTED: _____ APPROVED: _____
 RECOMMENDED: _____ CHIEF, WATERWAYS MAINTENANCE SECTION
 CHIEF, SURVEY SECTION _____ SURVEYED: _____ PLOTTED: _____ CHECKED: _____
 CB_05_CB5X_20240228_CS

THE EXISTING PROJECT
 The existing project provides for a channel across the outer bar 47 feet deep and of suitable width with dimensions gradually reducing to river mile 1.0 at Gunn's Rock; then a channel 37 feet deep and 300 feet wide to the railroad bridge at river mile 9.0; then a channel 37 feet deep and 400 feet wide to river mile 15.0 in Inham's Slough.
 Also provides for a turning basin 37 feet deep, 900 feet wide and 1000 feet long at North Bend and Coalbank Slough.