





O R E G O N

LEGEND

- Federal Navigation Channel
- Federal Navigation Channel Centerline
- Pipeline, Submarine On Land Line
- Cable, Overhead
- Cable, Submarine
- Pipeline, Overhead
- Anchorage Area
- Dredged Material Placement Area
- Cable Area
- Pipeline Area
- Shoaling Area
- Buoy, Lateral
- Buoy, Cardinal
- Buoy, Isolated Danger
- Buoy, Safe Water
- Buoy, Special Purpose
- Beacon, General
- Shoalest Sounding**
- Benchmark
- Pylon Bridge Support
- Obstruction Point
- Wreck-Submerged
- Staff Gage
- Recording Gage

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Oregon North Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water. MLWL is 0.26 feet below the North American Vertical Datum (NAVD 88 Geoid 09) at Columbia River Mile 2.0.

River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission, July 1972.

The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general channel conditions existing at that time and is in support of channel maintenance only.

** Shoalest Sounding per Quarter per Reach

STAFF GAGE AT HAMMOND: Northing: 943276 Easting: 7328236

CONDITION ☒ PREDREDGE ☐ POSTDREDGE ☐

COLUMBIA AND LOWER WILLAMETTE RIVERS
BELOW VANCOUVER, WASH. AND PORTLAND, OREG.
COLUMBIA RIVER
MCR-NJ1 AND SWS DISPOSAL SITES
18 August 2025

SCALE IN FEET
0 1,000 2,000 3,000 4,000 5,000

SUBMITTED: _____ APPROVED: _____
RECOMMENDED: _____ CHIEF, WATERWAY'S MAINTENANCE SECTION
CHIEF, SURVEY SECTION SURVEYED: _____ PLOTTED: _____ CHECKED: _____
CL_00_SWS_20250818_PA