



NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Oregon South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water 1983-2001. MLLW is 0.47 feet below the North American Vertical Datum (NAVD 88) at the Coast Guard Dock, and 0.29 at Boat Basin.
 River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission, June 1968.
 The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general channel conditions existing at that time and is in support of channel maintenance only.
 ** Shoalest Sounding per Quarter per Reach
 STAFF GAGE AT COAST GUARD DOCK: Northing: 301879 Easting: 3862088
 STAFF GAGE AT ROGUE BOAT BASIN: Northing: 299748 Easting: 3862655
 CONDITION PREDREDGE POSTDREDGE

LEGEND			
	Federal Navigation Channel		Benchmark
	Federal Navigation Channel Centerline		Pylon Bridge Support
	Pipeline, Submarine On Land Line		Rock
	Cable, Overhead		Obstruction Point
	Cable, Submarine		Wreck-Submerged
	Pipeline, Overhead		Staff Gage
	Anchorage Area		Recording Gage
	Dredged Material Placement Area		Beacon Lateral
	Cable Area		Shoalest Sounding**
	Pipeline Area		
	Shoaling Area		

2010 Aerial Photography data source: ESRI, USDA, NASA, i-cubed - Reference is Navigation Chart No. 18601

ROGUE RIVER, OREGON
DISPOSAL SITE
 21 May 2024

SCALE IN FEET
 0 500 1,000 1,500 2,000 2,500

SUBMITTED: _____ APPROVED: _____
 RECOMMENDED: _____ CHIEF, WATERWAYS MAINTENANCE SECTION
 CHIEF, SURVEY SECTION _____ SURVEYED: _____ PLOTTED: _____ CHECKED: _____
 RO_00_ROD_20240521_PA