



NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Oregon South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water 1983-2001. MLLW is 0.47 feet below the North American Vertical Datum (NAVD 88) at the Coast Guard Dock, and 0.29 at Boat Basin.
 River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission, June 1968.
 The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general channel conditions existing at that time and is in support of channel maintenance only.
 ** Shoalest Sounding per Quarter per Reach
 STAFF GAGE AT COAST GUARD DOCK: Northing: 301879 Easting: 3862088
 STAFF GAGE AT ROGUE BOAT BASIN: Northing: 299748 Easting: 3862655
 CONDITION PREDREDGE POSTDREDGE

LEGEND	
	Federal Navigation Channel
	Federal Navigation Channel Centerline
	Pipeline, Submarine On Land Line
	Cable, Overhead
	Cable, Submarine
	Pipeline, Overhead
	Shoaling Area
	Anchorage Area
	Dredged Material Placement Area
	Cable Area
	Pipeline Area
	Buoy, Lateral
	Buoy, Cardinal
	Buoy, Isolated Danger
	Buoy, Safe Water
	Buoy, Special Purpose
	Beacon Lateral
	Contour Lines
	Shoalest Sounding**
	Benchmark
	Pylon Bridge Support
	Rock
	Obstruction Point
	Wreck-Submerged
	Staff Gage
	Recording Gage

ROGUE RIVER SOUTH JETTY

STAFF GAGE

PORT OF GOLD BEACH

THE EXISTING PROJECT
 The existing project provides for a small boat access channel 110 feet deep and 100 feet wide.
 *Presently maintained to 8 feet.

ROGUE RIVER, OREGON
ENTRANCE TO BOAT BASIN
 15 July 2024
 SCALE IN FEET
 0 100 200 300 400 500
 SUBMITTED: _____ APPROVED: _____
 RECOMMENDED: _____ CHIEF, WATERWAYS MAINTENANCE SECTION
 CHIEF, SURVEY SECTION _____ SURVEYED: _____ PLOTTED: _____ CHECKED: _____
 RO_02_ROB_20240715_CS
 3,864,000