



NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Oregon South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum:
 Soundings are shown in feet and indicate depths below Mean Lower Low Water 1983-2001. MLLW is 0.00 feet below the North American Vertical Datum (NAVD 88) at Light 21.
 River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission, June 1968.

THE EXISTING PROJECT
 The existing project provides for an entrance channel 26 feet deep and of suitable width across the outer bar; thence a channel 22 feet deep and 200 feet wide from the entrance to a turning basin 22 feet deep, 600 feet wide, and 1000 feet long at Reedsport.
 Also provides for a side channel 22 feet deep and 200 feet wide from the main channel at river mile 8 to a turning basin 22 feet deep, 500 feet wide, and 800 feet long at Gardiner.

LEGEND

	Federal Navigation Channel		Buoy, Lateral		Benchmark
	Federal Navigation Channel Centerline		Buoy, Cardinal		Pylon Bridge Support
	Pipeline, Submarine On Land Line		Buoy, Isolated Danger		Obstruction Point
	Cable, Overhead		Buoy, Safe Water		Wreck-Submerged
	Cable, Submarine		Buoy, Special Purpose		Staff Gage
	Pipeline, Overhead		Beacon, General		Recording Gage
	Anchorage Area		Contour Lines		Shoalest Sounding**
	Dredged Material Placement Area				
	Cable Area				
	Pipeline Area				
	Shoaling Area				

UMPQUA RIVER, OREGON
CANNERY SANDS
 09 December 2024

SCALE IN FEET
 0 300 600 900 1,200 1,500

SUBMITTED: _____ APPROVED: _____
 RECOMMENDED: _____ CHIEF, WATERWAYS MAINTENANCE SECTION
 CHIEF, SURVEY SECTION _____ SURVEYED: _____ PLOTTED: _____ CHECKED: _____

UM_05_UMS_20241209_CS