



Yaquina River

Overhead Pipeline  
61.9 ft. Clearance (MLLW)

Overhead Pipeline  
26 ft. Clearance (MLLW)

PILING AREA

PILING AREA

STAFF GAGE

SUBMARINE PIPELINE  
CROSSING AREA

1404-02-B

20

1404-02

1404-02-A

TOLEDO

PILING AREA

PILING AREA

STAFF GAGE

LEGEND

- |                                       |                       |                      |
|---------------------------------------|-----------------------|----------------------|
| Federal Navigation Channel            | Buoy, Lateral         | Benchmark            |
| Federal Navigation Channel Centerline | Buoy, Cardinal        | Pylon Bridge Support |
| Pipeline, Submarine On Land Line      | Buoy, Isolated Danger | Rock                 |
| Cable, Overhead                       | Buoy, Safe Water      | Obstruction Point    |
| Cable, Submarine                      | Buoy, Special Purpose | Wreck-Submerged      |
| Pipeline, Overhead                    | Beacon, General       | Staff Gage           |
| Anchorage Area                        | Contour Lines         | Recording Gage       |
| Dredged Material Placement Area       |                       | Shoalest Sounding**  |
| Cable Area                            |                       |                      |
| Pipeline Area                         |                       |                      |
| Shoaling Area                         |                       |                      |

Image Copyright 2015 DigitalGlobe Inc. - Reference is Navigation Chart No. 18581 and 18561

NOTES:

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83-2011), projected to the State Plane Coordinate System (SPCS), Oregon North Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Lower Low Water 1983-2001. MLLW is 1.31 feet below the North American Vertical Datum (NAVD 88) at Toledo, 1.31 feet at Coffey Dam.

River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission, June 1968.

The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general channel conditions existing at that time and is in support of channel maintenance only.

\*\* Shoalest Sounding per Quarter per Reach

STAFF GAGE AT TOLEDO: Northing: 365493 Easting: 7307264  
STAFF GAGE AT COFFEY DAM: Northing: 366150 Easting: 7306954

THE EXISTING PROJECT

The existing project provides for a channel 10 feet deep and 200 feet wide, and approximately 1800 feet long in Depot Slough.

YAQUINA RIVER,  
OREGON

DEPOT SLOUGH

22 September 2026

SCALE IN FEET

0 125 250 375 500

SUBMITTED:

APPROVED:

RECOMMENDED:

CHIEF, WATERWAYS MAINTENANCE SECTION

CHIEF, SURVEY SECTION

SURVEYED: \_\_\_\_\_ PLOTTED: \_\_\_\_\_ CHECKED: \_\_\_\_\_

YB\_07\_DSL\_20260922\_CS

366,000

7,305,000

364,000

7,305,000

364,000

7,307,000

365,000

7,308,000

7,308,000